



CAMPOLIN F

CAMPOLIN F is a ready-to-use emulsion of acrylic rubber copolymer, reinforced with polypropylene fibers. After drying, forms a waterproof elastic film protecting support from infiltrations. Its reinforced formula facilitates the application, specially for the upstands, as it is no longer necessary additional fiber glass reinforcement.

User application

CAMPOLIN F is a coating for sealing and repairing roofs, terraces and facades. Avoid leaks and humidity, excellent elasticity and good aging resistance against attacks like the gel or UV. Avoid the carbonation of the concrete. For accessible roofs, pedestrian terrace or technical roofs. Support concrete, brick, tiles and ceramic tile.

RESTRICTIONS ON USE:

Not suitable for basins, tanks and in general for any kind of reservoir.

Untreated anti-root. Not suitable for planters.

Do not apply under heavy protection. Not realize screed on CAMPOLIN F®.

Do not replace a bituminous waterproofing membrane.

Composition

	CAMPOLIN F
Dry content	61-63 %
Density at 20°C	1.30 - 1.35
Viscosity	130 +/- 5
Yield	Approx. 750 g/m2 per layer
Drying time for touch up	1 hour
Total drying time	24 hours
Disponibile colours	Terracotta - Dark grey - White - green



Class P3 product according to the ETAG 005 guide of EOTA relative to liquid waterproofing systems.

Suitable for roof and terraces with pedestrian access.

Test results available on request.



Packaging

	CAMPOLIN F
Packaging	Drums of 5 or 20 kg
Consumption	On rough and absorbent substrate (i.e concrete) : - 5 kg can cover about 5 m² - 20 kg can cover about 20 m² Apply in two layers.
Storage	The product can be stored until 12 months at a temperature between 5°C and 35°C in closed original packaging and protected from the sun. This product, however, contains frost-preventing properties, allowing it to be stored for a few days at 0°C.

Installation

Before use, well homogenize **CAMPOLIN F**, by stirring product in the can. The tools used (roll, brush, rubber squeegee) must be clean, not soiled by solvent because it might break the emulsion.

CAMPOLIN F must be applied on dry, clean surfaces, free of all dust and non-adhesive parts, and previously degreased). Very dry and absorbent substrates must first be moistened before application to avoid insufficient adhesion. **CAMPOLIN F** cannot be applied in rainy conditions.

APPLICATION: In 2 layers after homogenization of the product.
Apply easily to the wool roller or brush. Spread first layer generous and uniform.
Let dry for 24 hours and apply the second layer.

Cleaning tools:

Fresh product: water.

Special indications

Hygiene, health and environment:

- Close cans properly after each use.
- Nonflammable product.
- Do not swallow.
- Do not throw wastes into sewers.

For further information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.