



Weber SL

Protective Waterproofing
Resin Finish

Flooring

PRODUCT

Weber SL is a solvent-based or water-based resin sealer designed to provide a durable, waterproof, and UV-resistant finish for decorative concrete surfaces. It enhances surface color, protects against moisture, stains, and wear, and leaves a glossy or satin sheen depending on application.

SCOPE OF USE

- Stamped or printed concrete
- Concrete pavements and walkways
- Exterior driveways and patios
- Concrete blocks and paving stones
- Decorative concrete floors (interior and exterior)

ADVANTAGES

- Waterproof and stain-resistant surface protection
- Enhances color depth and visual appeal
- UV-stable, resists yellowing and fading
- Quick drying with excellent adhesion
- Suitable for high-traffic and outdoor areas

APPLICABLE STANDARDS

EN 1504-2

TECHNICAL SPECIFICATIONS

Appearance

White Liquid

Coverage

5 – 8 m² per kg per coat (depending on surface porosity)

Touch Dry Time

1 – 2 hours

Recoat Time

4 – 6 hours

Full Cure Time

24 – 48 hours

Water Resistance

Fully waterproof after full cure

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

- Ensure the surface is dry, clean, and free of dust, oil, and loose particles
- If applied over stamped concrete (e.g., with Weber DM), wait at least 24–48 hours after washing off the release agent
- Do not apply on damp surfaces or if rain is expected within 24 hours

RECOMMENDATIONS FOR USE

- Application temperature between 5 and 35°C.
- Do not dilute with water.
- Do not apply the first coat of weber SL until at least 72 hours have passed since the completion of the floor.
- Application by spray or roller just after cleaning the substrate from weber DM with pressurized water.
- The second hand of weber SL shall be applied after the first hand has dried.
- weber.floor print or weber.floor decor can be used for preservation and maintenance of the floor.

PRODUCT APPLICATION

- Stir thoroughly before use. Do not dilute unless advised.
- Apply evenly using a roller, brush, or low-pressure sprayer.
- For best results, apply two coats in opposite directions.
- Avoid pooling or over-application.
- Protect area from foot traffic and water until fully cured

PRECAUTIONS

- Apply in well-ventilated areas.
- Wear gloves, goggles, and mask when handling.
- Do not apply under direct sun or in extreme heat.
- Keep away from open flame (for solvent-based versions).
- Keep out of reach of children. Refer to SDS for safety.

STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

SAFETY PRECAUTIONS

The product irritates the eyes, airways and skin. Wear goggles with lateral protection, dust mask in areas with limited ventilation, proper work clothing and protective gloves. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

NOTE

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

DISCLAIMER

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Ghana. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.